

RIXSON[®]**ASSA ABLOY**

Heavy-Duty Offset Hung Floor Closers

Model 20 3/4" Offset

Application

- Single Acting, Handed
- Interior Doors
- Weight to 200 lbs.*
- Door Width up to 3'0"



ANSI/C06042/C06052

* Door size & weight guidelines are determined using the appropriate number of intermediate pivots

Product Description & Features

- Allows 180° door swing (*trim permitting*)
- Single valve adjustable closing speed 70° to 0°
- Built-in hydraulic backcheck cushions opening from 140° to 180°
- Available non-hold open only
- Delayed action not available
- Models available to meet ICC/ANSI A117.1 low opening force requirements, prefix "PH". (For 8-1/2 lbs. of opening force prefix "PH" and suffix "8-1/2 lbs.")
- Available with floor plate or threshold installation (*floor plate shown*)
- Cast iron cement case
- Vertical door adjustment
- Standard top pivot: #180 included
- Intermediate pivot(s) recommended: M19 (*order separately*), see page 17
- Doors up to 90" (2286mm) in height should use one intermediate pivot. Each additional 30" (762mm) warrants another intermediate pivot
- For fire rated openings (*up to 3 hour assemblies*) prefix F. This package will be supplied with a steel top pivot (F180) and non hold open closer. Intermediate pivot required; FM19 (*order separately*). See page 17
- Fire rated closers cannot have PH option
- For 20-minute labeled doors suffix -20 to the part number
- Furnished with wood and machine screws
- Extended spindles available in 1/2" increments up to 2" longer than standard

Technical Information

Frame stop required

