

Model 50 x 554 Arm

Application

- Single Acting, Handed
- Interior Doors
- Concealed Arm
- Weight to 250 lbs.
- Door Sizes up to 4'0" x 8'0" (1219x2438mm)



ANSI/CO6022

Product Description & Features

Concealed arm is designed to eliminate visible adjusting screws on face of door

- Arm bolt locks arm to closer spindle – adjustment made through heel of door
- Interchangeable spindle adapters
- Separate and independent valves for closing speed, latch speed and backcheck
- Available non-hold open (N) or automatic hold open (A) specify 90° or 105°
- Delayed action option – prefix "DA" (*non-hold open only*) closer will not have backcheck
- Order spring sizes 3 through 5:

Model	Door Width
5013 x 554	36" (914mm)
5014 x 554	42" (1067mm)
5015 x 554	48" (1219mm)

- Models available to meet ICC/ANSI A117.1 low opening force requirements. Prefix "PH"

Model	Door Width
PH5012 x 554	42" (1067mm)
PH5013 x 554	48" (1219mm)

- Available with floor plate or threshold installation (*floor plate shown*)
- Cylolac, rustproof cement case
- Standard top pivot #340 included
- Not allowed for fire rated doors
- Frame stop required at lock edge. If not supplied by frame manufacturer, recommend use of 60131 (*see Door Control Accessories, page 92*)
- Furnished with wood and machine screws
- Extended spindles available in 1/2" increments up to 2" longer than standard

Technical Information

Frame stop required at lock edge

